



**NOTES:**

- RECEPTACLE CONTACTS ARE INSERTED INTO A NYLON SHELL PRIOR TO OVERMOLDING.

**PROPRIETARY INFORMATION  
KORD KING, INC.  
ALL RIGHTS RESERVED**

<p align="center"><u>TOLERANCES</u></p> <p>FRACTIONAL ± 1/16 2 PLACE DEC. ± 0.030 3 PLACE DEC. ± 0.015</p>		<p>KORD KING COMPANY, DIVISION OF KING ASSOCIATES, 62 INDUSTRIAL CIRCLE, LANCASTER, PA 17601, UNITED STATES OF AMERICA</p>					
<p>DIMENSIONS ARE IN INCHES DIMENSIONS IN ( ) ARE IN MM</p>		<p>NAME: A.Eachus      DATE: 07/29/19</p>		<p>ITEM NUMBER</p> <p align="center"><b>NEMA L7-15R</b></p>			
<p align="center"><u>APPROVALS</u></p> <p>UL File # E-76388</p>		<p>DRWN:      CKD:      APPRV:</p>		<p>TITLE:</p> <p align="center"><b>NEMA TWIST LOCK L7-15R</b></p>		<p>SIZE: <b>A</b>      SCALE: <b>FULL</b>      DWG No. <b>KKL7-15R</b>      REV: <b>A</b></p>	
<p>THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF KORD KING AND ITS RECEIPT OR POSSESSION DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE OR SELL ANYTHING IT MAY DESCRIBE. REPRODUCTION, DISCLOSURE, OR USE WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF KORD KING IS STRICTLY FORBIDDEN.</p>		<p align="center">MATERIAL SPEC</p> <p>RATING: <b>277V , 15A</b></p> <p>PLUG MATERIAL: <b>PVC</b></p> <p>CONTACT MATERIAL: <b>BRASS</b></p>		<p>DO NOT SCALE PRINT</p>			